



Cuerpo / Body	Fund. Nodular / Nod. Cast Iron (GGG40.3)
Asientos / Body Seat	Inox/ S. Steel (AISI420)
Asiento Disco / Disk Seat	Inox/ S. Steel (AISI420)
Tornilleria / Bolting	Acero/ Steel
Volante / Hand Wheel	HºFº (GG25) o Aluminio / Cast Iron (GG25) or Aluminium

- Cuerpo/Tapa: EN 13789, Body / Bonnet: EN 13789.
- Distancia entre bridas EN 558 Serie8(DIN-3202/F32)) / EN 558 Series 8 Face to Face (DIN-3202/F32)).
- Bridas dimensionadas EN 1092-2 (DIN 2501) /Flanges to EN 1092-2 (DIN 2501)

DN	REF	D	L	H abierto / H open	V	X	Y	Peso [Kg] / Weight
[mm]								
15	V279DR915	95	90	201	100	160	95	5
20	V279DR920	105	95	210	100	160	95	5
25	V279DR925	115	100	201	100	160	95	7
32	V279DR932	140	105	246	150	170	95	10
40	V279DR940	150	115	242	150	170	95	12
50	V279DR950	165	125	242	150	170	95	14
65	V279DR965	185	145	286	200	175	125	20
80	V279DR980	200	155	286	200	175	125	25
100	V279DR910	220	175	307	200	180	185	35
125	V279DR912	250	200	375	250	195	200	80
150	V279DR915	285	225	400	300	195	215	82